



1.1	1.2	1.3				1.4	1.5	1.6	1.7	1.8			
		PIPE	SCH.	L	A					LITRES	PD (BAR)	TD (°C)	TEST PRESSURE
REF.	Nº CONNEX. M. 1/4"	SIZES					(1) (2)	(1)	PT (BAR)	PIPE	CAPS	NIPPLES	
1	C-24010A	10	40	674	67	1.42	35	250	54	A106B	A105	A106B	
	C-24016A	16	40	1034		2.20	22		34				
	C-28010A	10	80	674		1.24	40		61				
	C-28016A	16	80	1034		1.92	25		39				
	C-34010A	10	40	693		3.18	15		23				
	C-34016A	16	40	1053		4.90	10		16				
	C-38010A	10	80	710	85	4.87	17		26	A234 WPB	A106B	A106B	
	C-38016A	16	80	1070		4.40	11		17				
	C-24010S	10	40	674		1.42	35		76				A312 TP 316L
	C-24016S	16	40	1034	2.20	22	48						
	C-28010S	10	80	674	1.24	40	87						
	C-28016S	16	80	1034	1.92	25	55						
	C-34010S	10	40	693	3.18	15	33						
	C-34016S	16	40	1053	4.90	10	22						
	C-38010S	10	80	710	85	4.87	17	37	A240 316L	A312 TP 316L			
	C-38016S	16	80	1070		4.40	11	24					
EUROPEAN DIRECTIVE APPLICATION 2014/68/UE													
2	2.1	FLUID: GROUP 2 (Water, steam, air and other) according to DIRECTIVE 67/548/CEE											
	2.2	CLASS ACCORDING TO DIRECTIVE: ART.4.3 DESIGN SUPPORT NORM: ACCORDING TO ART.4.3											
3	FINISH	STAINLESS STEEL POTS: Pickling											
		CARBON STEEL POTS: Base coating and blue synthetic enamel											

(1) Design pressure (PD) and temperature (TD).
 (2) Maximum design pressures accepted by PED for recipients ART.4.3 at higher pressure they correspond to recipients of the class to determine depending on the corresponding design pressure.
 (3) Paint finish not suitable for temperatures above 100 °C (contact factory).

All NPT threaded connections in (ANSI/ASME B1.20.1)

CHARACTERISTICS PLATE