



REF.	SIZES				VOL. LITRES	MAT.	PERMISSIBLE MAXIMUM CONDITIONS											
	PIPE	SCH.	L	A			TEMP.	UP TO 38°C	100°C	200°C	300°C	400°C	427°C	454°C	500°C			
								PRESSURE (BAR)										
1	P-2401A	2"	40	250	75	CARBON STEEL	PRESSURE (BAR)	140	140	140	140	108	90	73	39			
			80					208	208	208	157	131	106	57				
	P-3401A	3"	40	150	-			135	135	135	135	102	85	69	37			
			80					193	193	193	145	121	98	52				
	P-3402A	3"	40	250	45			1	135	135	135	135	102	85	69	37		
			80					193	193	193	145	121	98	52				
	P-4401A	4"	40	300	55			2.23	28	28	28	28	28	28	28	28		
			80					1.98	28	28	28	28	28	28	28	28		
	1	P-2401S	2"	40	250			75	316L STAINLESS STEEL	PRESSURE (BAR)	140	117	98	88	82	80	78	-
				80							204	171	143	128	119	117	114	-
P-3401S		3"	40	150	-	0.6	132	111			93	83	77	76	74	-		
			80			188	158	133			119	110	108	106	-			
P-3402S		3"	40	250	45	1	132	111			93	83	77	76	74	-		
			80			188	158	133			119	110	108	106	-			
P-4401S		4"	40	300	55	2.23	28	28			28	28	28	28	28	28		
			80			1.98	28	28			28	28	28	28	28	28		
P-4801S		4"	40	300	55	2.23	28	28			28	28	28	28	28	28		
			80			1.98	28	28			28	28	28	28	28	28		
2	FLUID:	GROUP 2 (Water, steam, air and other) according to DIRECTIVE 67/548/CEE																
3	FINISH	STAINLESS STEEL POTS:						Pickling										
		CARBON STEEL POTS:						Base coating and blue synthetic enamel										

Note.-

- 1) For pressures and temperatures not reflected on table, point 1.5, please contact with your authorized **mecesa** agent.
- 2) Paint finish not suitable for temperatures above 100 °C (contact factory).

CHARACTERISTICS PLATE

